

TOP QUALITY PALLET TRUCK

- Top class range of pallet trucks with excellent designs
- Professional and ideal storage aid for all variety of manual transport tasks over short distances in stores and warehouse as well as factory plants.
- Reliable, sturdy, torsion-resistant due to its extremely strong high quality steel profile Germany standard WAGNER painting system ensures best powder coating and painting quality.
- All pivots points are greased ensures excellent maneuverability with effortless steering The chromed bearing bushes and joints ensure quiet running properties and particularly long service life.

| Hand pallet truck 1KG=2.2LB 1INCH=25.4MM | | | | | | | |
|--|----|-----------------------------|-----------------|----------|-------------------------|----------|------------------|
| ltem/Type | | AC20 | | AC25 | | AC30 | |
| Capacity Q | kg | 2000 | | 2500 | | 3000 | |
| Min. fork height h | mm | 85 | 75 | 85 | 75 | 85 | 75 |
| Max. fork height h. | mm | 200 | 190 | 200 | 190 | 200 | 190 |
| Steering wheel | mm | ф 200x5 0 | ф 180x50 | ф 200x50 | ф 180x50 | 4 200x50 | ф 180x5 |
| Load roller Single | mm | ф 80х93 | ф74 x9 3 | ф 80х93 | ф 74 х9 3 | ф 80х93 | ф 74х93 |
| Load roller Tandem | mm | ф80x70 | ф74 x 70 | ф 80x70 | ф 7 4 x70 | ф 80x70 | ф 7 4 x70 |
| Size of fork e*s | mm | 160x50 | | | | 160x60 | |
| Width overall forks B | mm | 450/520/540/685 | | | | | |
| Fork length | mm | 800/900/1000/1100/1150/1220 | | | | | |



 Option of single and tandem fork rollers
 Additional entry and exit fork rollers guarantees for maximum stability and safety for transporting goods



Excellent galvanized whole casting hydraulic pump, robust and durable, with fine control of lowering speed and overload valve, low routine maintenance.







- Ergonomically designed handle with comfortable rubber grip allows the optimized safety as well as comfortable. Three position operational handle lever for lifting, transporting and lowering purposes
- Lower Position----to lower load, pull up on the finger tip control
- Neutral Position—to place finger tip control in this position during pulling the truck or load
- Lift Position—to raise load, push down on finger tip control, pump handle to raise the load





- Option of different coating material for both steering wheel and fork rollers
- Polyurethane----Ideal for delicate floors with hard wearing and non-marking property, quiet and durable
- Nylon---low drag efforts, high resistance to chemicals, non-marking, preferred in food, fishing and chemical industries with smooth level floors.
- Rubber---Best choice for quiet and durable demands, ideal for smooth and rough floors.